

# Intrinsically Safe Permissible

## Multi-Function Dual-Light™ Angle Light w/ Multi-Angle Magnetic Base - Rechargeable

This Rechargeable XPR-5572RM Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light w/ Multi-Angle Magnetic Base is cULus and MSHA certified Intrinsically Safe Permissible. This is a Flashlight, a Floodlight and a Dual-Light Angle Light all in one super rugged design. The flashlight setting offers 3 user-selectable brightness settings of high, medium and low, plus a strobe feature. The beam distance rating on the flashlight's high-brightness setting is 267 meters (more than 875 feet) thanks to the high-efficiency deep parabolic reflector. This ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The 5572RM had two additional features that don't exist in any competitive product. First is the Floodlight, with its own 3 user-selectable brightness settings of high, medium and low, the floodlight is outstanding at lighting up objects in the immediate vicinity. The low-brightness floodlight setting, "Survival Mode", provides just enough light in an emergency situation with an impressive run-time of 30 hours. Plus, the 5572RM utilizes Nightstick's exclusive Dual-Light mode... the ability to turn on the flashlight and the floodlight at the same time. With this setting, the user can simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work. The included Multi-Angle Magnetic Base allows the light to slide and lock into place giving it an additional level of functionality. The powerful Rare-earth Magnet with its rubber protective covering attaches to virtually any ferrous metal surface. The single point locking lever can be used in conjunction with the gimbal head to focus the light exactly where it's needed. Power comes from a rechargeable Lithium-ion battery.

**INTRINSICALLY SAFE  
PERMISSIBLE**



**200** Flashlight Lumens

**200** Floodlight Lumens

**200** Dual-Light™ Lumens



TECHNOLOGY



XPR-5572RM



- cULus and MSHA certified Intrinsically Safe Permissible
- Flashlight/Floodlight/Dual-Light™
- Includes Multi-Angle Magnetic Base
- User-selectable brightness settings on Flashlight & Floodlight including 20 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009) mounted in any position

# Intrinsically Safe Permissible

## FEATURES

- cULus and MSHA certified Intrinsically Safe Permissible
- CREE® LED technology – 50,000+ hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the Flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the Floodlight including a 20 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled Nylon Polymer housing
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Battery charge status indicator (for use only with rechargeable battery)
- Multi-Angle Magnetic Base w/ powerful Rare-earth Magnet and locking gimbal head
- Waterproof
- Impact & chemical resistant
- Light (w/o magnetic base) meets the requirements of NFPA-1971-8.6 (2013)
- Charger meets the requirements of NFPA-1901 (2009) mounted in any position
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery pack (included)
- Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)
- Limited Lifetime Warranty\*



High-efficiency deep parabolic reflector



Wide-beam floodlight



Heavy-duty stainless-steel pocket clip



Wall or vehicle mounted charger

Permissible Nightstick XPR-5572 Flashlight/Floodlight

**MSHA** APPROVAL No. 20-A150005-0  
TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

**WARNINGS:** Do not charge in hazardous location. MSHA approved for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or L91 batteries. Replace the Battery Pack in fresh air only. Do not mix batteries from different manufacturers or different types. Battery Pack to be replaced by a qualified technician only. The Model Nightstick 5572 must not be opened in areas where permissibility is required. Substitution of components may impair Intrinsic Safety.

**UL** LISTED E 467750 0359

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

UL listed for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or L91 batteries.

CLASS I DIV 1 GRPS A-D T3  
CLASS II & III DIV 1 GRPS E-G  
CLASS I ZONE 0 Group IIC T3  
CLASS II ZONE 20 Group IIC T3  
-20°C ≤ Tamb ≤ +70°C



Multi-Angle Magnetic Base w/ powerful Rare-earth Magnet and locking gimbal head

## SPECIFICATIONS

- Lumens: flashlight high-200, medium-100, low-60, floodlight high-200, medium 100, survival 20, dual-light-200
- Run-time: flashlight high-6 hrs, medium-11 hrs 30 min, low-22 hrs 30 min, floodlight high-6 hrs, medium-11 hrs 30 min, survival-30 hrs, dual-light-6 hrs
- Recharge time: 6 hours
- Beam distance: 267 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7.6in, width: 3.2in, depth: 3in, bezel diameter: 2.8 in, weight: 24.9oz w/ magnetic base

FL1 STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	200 LUMENS	200 LUMENS	100 LUMENS	60 LUMENS
	8h	6h	11h	22h
	235m	267m	199m	145m
	13836cd	22249cd	14828cd	7790cd
	2m			
	1m			

## INCLUDED

- Angle Magnetic Base
- Rechargeable Lithium-ion Battery Pack
- Wall or Vehicle Mounted Charger
- AA Battery Carrier (AA batteries not included)
- AC & DC Power Supplies

Model	UPC 0 17398
XPR-5572RM	80466 0



## SAFETY RATING

cULus and MSHA certified Intrinsically Safe Permissible

XPR-5572RM

